Amendments to the Specification:

Please replace the paragraph beginning at page 1, line 26, with the following rewritten paragraph:

A recreational vehicle suite has a combination bed and sofa, a floor, a side wall and an end wall. A TV viewing screen is located in the proximity of the of the end wall for viewing from the bed and sofa.

Please replace the paragraph beginning at page 3, line 20, with the following rewritten paragraph:

A structural metal frame 54 is located on the underneath side of the support panels 48 and 50 as best shown in Fig. 3. A first portion 56 of the frame 46-54 is secured at any convenient way to the panel 48, and a second portion 58 of the frame is secured in any convenient way to the panel 50. An elongated hinge 60 extends between the portions 56 and 58 of the frame 54. An arm 62 is rigidly secured to the first frame portion 56 and extends vertically downwardly therefrom. An electric hoist 64 is rigidly secured to the second frame portion 58 and has a telescopic rod 66 extending outwardly therefrom towards arm 62 and is pivotally secured to arm 62 at point 68 in any convenient manner. An electric hoist 64 suitable for use in this invention is a 12 volt Linak model LA31. A wired or wireless control 70 is located adjacent the head portion 42 of the cushion/mattress 40 so that a person lying thereon can control the electric hoist 64. As shown in Figs. 4 and 5, the electric hoist 64 can exert pressure on arm Application No. 10/624,372 Docket No. P06636US0 Reply to Office Action of August 24, 2004

62 which will tilt the head portion 42 of the cushion/mattress 40, and the first frame portion 56 upwardly to the inclined position shown in Figs. 5 and 6.

Please replace the paragraph of the Abstract on page 7 with the following rewritten paragraph.

ABSTRACT OF THE DISCLOSURE

A recreational vehicle suite has a combination bed and sofa, a floor, a side wall and an end wall. A TV viewing screen is located in the proximity of the of the end wall for viewing from the bed and sofa. A bench is supported on the floor and has a head portion and a foot portion. An elongated normally horizontal cushion/mattress is mounted on a top of the bench and normally covers the bench including the head and the foot portions. The cushion/mattress has a head portion normally covering the head portion of the bench and is hingedly connected to a foot portion of the cushion/mattress. A power means is within the bench for tilting The bench is able to tilt the head portion of the cushion/mattress upwardly at an angle with respect to the bench.